cudy LT400

4G LTE N300 WiFi Router







- Cudy 4G WiFi Router 300Mps
- LTE speed up to 150 Mbps downstream and 50 Mbps upstream
- WiFi speed up to 300 Mbps
- Supports VPN for security connections
- Supports more than 15 DDNS for remote management
- 4G Watchdog
- WiFi scheduling supports configuration of available WiFi time
- Flexible WAN/LAN port for dual connectivity.



| Reference / Model | CUDY-37 / LT400 |
|--|-----------------|
| 4G LTE Cat 4 AC1200 4G LTE WiFi router | |
| 2 2.4G WiFi antennas (802.11n) | |
| 2 4G LTE antennas | |
| 5dBi gain | |
| WiFi Frequency: 2.412 GHz ~ 2.4835 GHz | |
| LTE FDD frequency bands: B1/B3/B7/B8/B20 (2100/1800/2600/900/800MHz) | |
| LTE TDD LTE frequency bands: B38/B40 (2600/2300MHz) | |
| Up to 150 Mbps downstream and 50 Mbps upstream LTE speed | |
| WIFi speed up to 300 Mbps | |
| IEEE 802.11n/b/g WiFi Standards | |
| Transmission power of <20dBm (CE) | |
| Wireless Modes: Wireless Radio On/Off, WMM | |
| Wireless Security: WEP, WPA/WPA2, WPA-PSK/WPA2-PSK | |
| | |

4G LTE N300 WiFi Router

| Reference / Model | CUDY-37 / LT400 |
|--|-----------------|
| OpenVPN / WireGuard / PPTP / L2TP | |
| Privacy protection thanks to DNS encryption via Cloudflare, NextDNS or Google | |
| Supports more than 15 DDNS for remote management | |
| Watchdog 4G feature allows automatic reactivation in case of disconnection | |
| WiFi scheduling allows configuring the WiFi time available | |
| 1 Nano SIM slot | |
| 3 RJ45 10/100 Mbps LAN Ethernet ports | |
| 1 10/100 Mbps Ethernet LAN/WAN RJ45 port | |
| 1 reset button | |
| Power supply: 12V DC / 1A | |
| Operating temperature: $0^{\circ}\text{C} \sim +40^{\circ}\text{C}$ (32°F $\sim +40^{\circ}\text{F}$) | |
| Operating relative humidity $5\% \sim 95\%$ | |
| Storage temperature from -20°C \sim +70°C | |
| Dimensions: 210 x 146 x 230 mm | |
| Weight: 700 g | |
| | |